



**Specifications** Ledvance LED Floodlight Max Radial 45 Aluminium Grey 1800W 268000lm 45D - 740 Cool White | IP66 - Symmetrical

[View Product](#)

## General Information

|                          |                                                      |
|--------------------------|------------------------------------------------------|
| SKU                      | 260252                                               |
| EAN                      | 4099854682605                                        |
| manufacturer_code        | 4099854682605                                        |
| Brand                    | Ledvance                                             |
| Manufacturer Name        | FLOODLIGHT MAX RADIAL SYMMETRIC 45 1800W 740 R45 WAL |
| Any Lamp all-in warranty | 5 Years                                              |
| Average Lifetime (h)     | 115000                                               |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Wattage                     | 1800W           |
| Replaces (Watt)             | 600             |
| Voltage (V)                 | 330             |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 740 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 70-79           |
| Colour of Light             | White           |
| Light Colour Options        | Single Color    |
| Luminous Flux (Lumen)       | 268000lm        |

|                       |                |
|-----------------------|----------------|
| Lumen per watt        | 149            |
| Beam Angle (degree)   | 45             |
| Tiltable              | No             |
| Power factor          | >0.93          |
| Product Type Category | LED Floodlight |

## Fixture Information

|                        |                       |
|------------------------|-----------------------|
| Mounting Method        | Ceiling, Wall mounted |
| Optical Cover          | Clear                 |
| Light Distribution     | Symmetrical           |
| IP-Rating              | IP66                  |
| Impact Protection (IK) | IK08 - 5 joules       |
| Colour of the Fixture  | Grey                  |
| Housing                | Aluminium             |
| Emergency Lighting     | No Emergency Unit     |

## Dimensions

|             |     |
|-------------|-----|
| Length (mm) | 800 |
| Width (mm)  | 660 |
| Height (mm) | 171 |

## Sensor Information

Type of sensor

**Why Any-lamp?**  
No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

